

WHAT IS CLAIMED IS:

1. An apparatus for enabling signal testing in a test configuration, comprising:

5 a cable environment embodied as a portable housing structure including a plurality of cables exhibiting a plurality of lengths and impedances, wherein at least a portion of each of the cables is supported within the portable housing structure and a user can selectively connect any one of the cables between a host device and a target device.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

10

2. The apparatus of claim 1, further comprising at least one signal measurement connector which is connectable to the cable environment, the at least one signal measurement connector including one or more test measurement points to enable collection of signal testing results.

15

3. The apparatus of claim 1, wherein the host device is a server.

4. The apparatus of claim 1, wherein the target device is a disk subsystem.

20

5. The apparatus of claim 1, wherein the cable environment includes a switch enabling a user to select a cable of a particular length and impedance.

SWS
A1

6. The apparatus of claim 1, wherein the signal testing is SCSI signal testing.

7. The apparatus of claim 1, wherein the test configuration is a Y-
5 configuration.

8. The apparatus of claim 1, wherein the test configuration is a cluster configuration.

10 9. The apparatus of claim 1, wherein the test configuration is a compatibility configuration.

10 10. The apparatus of claim 1, wherein the test configuration is a cascaded configuration.

15 11. A method for enabling signal testing in a test configuration, comprising steps of:

moving a cable environment to a location corresponding to the test configuration, wherein the cable environment is embodied as a portable housing
20 structure including a plurality of cables exhibiting a plurality of lengths and impedances; and

selectively connecting any one of the cables of the cable environment between a host device and a target device.

12. The method of claim 11, further comprising a step of collecting signal testing results by monitoring a signal measurement connector connected to the cable environment.

5

13. The method of claim 11, wherein the host device is a server.

14. The method of claim 11, wherein the target device is a disk subsystem.

10 15. The method of claim 11, wherein a user selects a particular cable of the cable environment for connection between the host device and the target device by input to a switch.

15 16. The method of claim 11, wherein the signal testing is SCSI signal testing.

17. The method of claim 11, wherein the test configuration is a Y-configuration.

20 18. The method of claim 11, wherein the test configuration is a cluster configuration.

19. The method of claim 11, wherein the test configuration is a compatibility configuration.

20. The method of claim 11, wherein the test configuration is a cascaded
5 configuration.

1003-0559-0001
AS
A2